




Addressable Sounder and Strobe 1-9403 / 1-9404









- 1. High sound level
- 2. Low power consumption
- 3. High intensity LED cluster
- 4. Remote start input can be used to drive with other systems
- 5. Programmable alarm mode, evacuate or alert/evacuate mode

- 6. Electronically addressable
- 7. Easy installation and connection.

Description

The I-9403 is a detachable, surface mounted sounder and strobe while the I-9404 is identical in appearance and features to the I-9403 but without strobe element. The audio efficiency and sound distribution generate over 85 dB at 3 meter distance giving an excellent audibility from the device location. Using six highlights LED's for high intensity visual alarm to warn the people. The GST sounder series are convenient plug and turn installing method, two part construction with base mounted termination allows easy installation and avoiding the wiring and connection problem associated with traditional sounder.



www.gst.uk.com info@gst.uk.com

Specification	
Specification	

Part Number	I-9403	I-9404	
Protection rating	IP 33		
Approval	LPCB,CE	CE	
Standard	EN54-part 3		
Sound level output	Alert Sound: 75dB; Evacuate sound: 85dB (at 3 meter)		
Main Sound Frequency	2.8Khz		
Strobe	6 highlight LED'	No feature	
Operating voltage	Loop 24vdc ; Power Supply 24Vdc(16~28Vdc)		
	Loop: standby 1mA/ alarm 5mA ;	Loop: standby 1mA/ alarm 5mA ; Supply	
Operating current	Supply current: standby 3mA / alarm	current: standby 3mA / alarm 35mA	
	65mA		
Operating Temperature	-10°C to 50°C @ 95% relative humidity		
Addressing Mode	Electronic programming with 1~242		
Application	Indoor and outdoor use		
Materials and colour	ABS / red; plexiglass / red		
Dimension	Ø 110mm x 97.5 mm		
Wiring	4 wires: 2 wires for loop (non-polarized); 2 wires for power cable(non-polarized)		

GST EnglandLion Court, Staunton Harold Hall, Melbourne Road, Ashby de la Zouch,
Leicestershire, England LE65 1RT Tel: +44 1283 225 478Fax: +44 1283 220 690GST DubaiZA04, Jebel Ali Free Zone, P.O.Box 17998, Dubai UAE
Tel: +971 (0)4 8833 050Fax: +971 (0)4 8833 053GST China80, Changjiang East Road, Economic & Technology Development Zone
Qinhuangdao, Hebei, China Tel: +86(0)335 850 2383Fax: +86 (0)335 850 7588










Sounder Installation

The sounder should be installed in compliance with all local codes or NFPA 72 National Fire Alarm Code, NFPA 70 National Electrical Code, BS5389 and EN54. It is installed onto a standard one gang electrical box with a mounting hole that has 6.5cm spacing.








Programming

The address and mode of sound level of the sounder can be programmed using GST handheld programmer (P-9910), purchased separately. Connect the two wires of the handheld programmer to Z1 (2), Z2 (4) terminals of the sounder.fig1



FIELD DEVICE PROGRAMMER

Selection of compatible Control Panels

Compatible with all GST Intelligent Fire Alarm Panels GST 100, GST 200, GST5000 and GST 9000.

Ordering Information:

Part No	Description	Weight /Kg	Pack Qty per Box
1-9403	Addressable Sounder and Strobe	0.360	45
1-9404	Addressable Sounder	0.361	45



Note: Specifications are subject to change without notice.

and Lion Court, Staunton Harold Hall, Melbourne Road, Ashby de la Zouch, Leicestershire, England LE65 1RT Tel: +44 1283 225 478 Fax: +44 1283 220 690

GST Dubai ZA04, Jebel Ali Free Zone, P.O.Box 17998, Dubai UAE Tel: +971 (0)4 8833 050 Fax: +971 (0)4 8833 053

> 80, Changjiang East Road, Economic & Technology Development Zone Qinhuangdao, Hebei, China Tel: +86(0)335 850 2383 Fax: +86 (0)335 850 7588




Wiring and Connection

Power Supply

Connect the wires to the required terminal according to the wiring diagram. The Z1, Z2 connect to addressable fire detection loop, non-polarized, the D1, D2 is for 24VDC power supply, non-polarized. The cable must be fire rated type and the size depends on the wiring distance and application. Minimum size gauge 1.0mm²(18 AWG)



www.gst.uk.com info@gst.uk.com



GST China